

PCTWORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : A61K 7/06	A1	(11) International Publication Number: WO 99/62468 (43) International Publication Date: 9 December 1999 (09.12.99)
(21) International Application Number: PCT/US98/11785 (22) International Filing Date: 4 June 1998 (04.06.98) (71) Applicant (for all designated States except US): THE PROCTER & GAMBLE COMPANY [US/US]; One Procter & Gamble Plaza, Cincinnati, OH 45202 (US). (72) Inventor; and (75) Inventor/Applicant (for US only): UCHIYAMA, Hirotaka [JP/JP]; 5-8-17-3B, Nishiokamoto, Higashinada-ku, Kobe 658-0073 (JP). (74) Agents: REED, T., David et al.; The Procter & Gamble Company, 5299 Spring Grove Avenue, Cincinnati, OH 45217 (US).		(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, GM, GW, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG). Published <i>With international search report.</i>
(54) Title: HAIR CONDITIONING COMPOSITION COMPRISING PRIMARY OIL AND SECONDARY OIL (57) Abstract Disclosed is a hair conditioning composition comprising: (1) a primary oil being water-insoluble, having a molecular weight of at least about 800, and in liquid form at 25 °C, the primary oil selected from the group consisting of: a) pentaerythritol ester oils, b) trimethylol ester oils, and mixtures thereof; (2) a secondary oil selected from the group consisting of: c) poly α -olefin oils, d) citrate ester oils, e) glyceryl ester oils, and mixtures thereof; and (3) an aqueous carrier.		

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

HAIR CONDITIONING COMPOSITION COMPRISING PRIMARY OIL AND SECONDARY OIL

5

TECHNICAL FIELD

The present invention relates to hair conditioning compositions comprising a primary oil and a secondary oil. More specifically, the present invention relates to hair conditioning compositions comprising a primary oil selected from certain high molecular weight ester oils.

BACKGROUND

Human hair becomes soiled due to its contact with the surrounding environment and from sebum secreted by the scalp. The soiling of the hair causes it to have a dirty or greasy feel, and an unattractive appearance. The soiling of the hair necessitates shampooing with regularity.

Shampooing cleans the hair by removing excess soil and sebum. However, shampooing can leave the hair in a wet, tangled, and generally unmanageable state. Once the hair dries, it is often left in a dry, rough, lusterless, or frizzy condition due to removal of the hair's natural oils and other natural conditioning and moisturizing components. The hair can further be left with increased levels of static upon drying which can interfere with combing and result in a condition commonly referred to as "fly-away hair", or contribute to an undesirable phenomena of "split ends", particularly for long hair.

A variety of approaches have been developed to alleviate these after-shampoo problems. These approaches range from post-shampoo application of hair conditioner such as leave-on and rinse-off products, to hair conditioning shampoos which attempt to both cleanse and condition the hair from a single product. Although some consumers prefer the ease and convenience of a shampoo which includes conditioners, a substantial proportion of consumers prefer the more conventional conditioner formulations which are applied to the hair as a separate step from shampooing, usually subsequent to shampooing. Conditioning formulations can be in the form of rinse-off products or leave-on products, and can be in the form of an emulsion, cream, gel, spray, and mousse. Such consumers who prefer the conventional conditioner formulations value the

relatively higher conditioning effect, or convenience of changing the amount of conditioning depending on the condition of hair or portion of hair.

A common method of providing conditioning benefit to the hair is through the use of hair conditioning agents such cationic surfactants and polymers, silicone conditioning agents, hydrocarbon oils, and fatty alcohols.

Cationic surfactants and polymers, hydrocarbon oils and fatty alcohols are known to enhance hair shine and provide moistness, softness, and static control to the hair. However, such components can also provide stickiness or greasy or waxy feeling, particularly when the hair is dried. Silicone conditioning agents are also known to provide conditioning benefits such as smoothness and combing ease due to the low surface tension of silicone compounds. However, silicone conditioning agents can cause dry feel or frizzy condition to the hair, again, particularly when the hair is dried.

Based on the foregoing, there remains a desire to provide hair conditioning compositions which provide improved conditioning benefits both when the hair is wet and when the hair is dried. Specifically, there is a need to provide long lasting moisturized feel, smooth feel, and manageability control to the hair when the hair is dried, yet not leave the hair feeling greasy.


None of the existing art provides all of the advantages and benefits of the present invention.

SUMMARY

The present invention is directed to a hair conditioning composition comprising:

(1) a primary oil being water-insoluble, having a molecular weight of at least about 800, and in liquid form at 25°C, the primary oil selected from the group consisting of:


a) pentaerythritol ester oils of the following formula:



wherein R¹, R², R³, and R⁴, independently, are branched, straight, saturated, or unsaturated alkyl, aryl, and alkylaryl groups having

from 1 to about 30 carbons;

- b) trimethylol ester oils of the following formula:




wherein R^{11} is an alkyl group having from 1 to about 30 carbons, and R^{12} , R^{13} , and R^{14} , independently, are branched, straight, saturated, or unsaturated alkyl, aryl, and alkylaryl groups having from 1 to about 30 carbons;

and mixtures thereof;


- (2) a secondary oil selected from the group consisting of:

- c) poly α -olefin oils derived from 1-alkene monomers having from about 6 to about 16 carbons, the poly α -olefin oils having a viscosity of from about 1 to about 35,000 cst, a molecular weight of from about 200 to about 60,000, and a polydispersity of no more than about 3;
- d) citrate ester oils being water-insoluble, having a molecular weight of at least about 500, and in liquid form at 25°C and having the following formula:



wherein R^{21} is OH or CH_3COO , and R^{22} , R^{23} , and R^{24} , independently, are branched, straight, saturated, or unsaturated alkyl, aryl, and alkylaryl groups having from 1 to about 30 carbons;

- e) glyceryl ester oils being water-insoluble, having a molecular weight of at least about 500, and in liquid form at 25°C and having the following formula:



wherein R^{41} , R^{42} , and R^{43} , independently, are branched, straight, saturated, or unsaturated alkyl, aryl, and alkylaryl groups having from 1 to about 30 carbons;

5 and mixtures thereof; and

(3) an aqueous carrier.

These and other features, aspects, and advantages of the present invention will become evident to those skilled in the art from a reading of the present disclosure.

10

DETAILED DESCRIPTION

While the specification concludes with claims which particularly point out and distinctly claim the invention, it is believed the present invention will be better understood from the following description.

15 All cited references are incorporated herein by reference in their entireties. Citation of any reference is not an admission regarding any determination as to its availability as prior art to the claimed invention.

Herein, "comprising" means that other steps and other ingredients which do not affect the end result can be added. This term encompasses the terms
20 "consisting of" and "consisting essentially of".

All percentages, parts and ratios are based upon the total weight of the compositions of the present invention, unless otherwise specified. All such weights as they pertain to listed ingredients are based on the active level and, therefore, do not include carriers or by-products that may be included in
25 commercially available materials.

The aspects and embodiments of the present invention set forth in this document have many advantages. For example, the hair conditioning compositions of the present invention provide long lasting moisturized feel, smooth feel, and manageability control to the hair when the hair is dried, yet not
30 leave the hair feeling greasy. The hair conditioning compositions of the present invention are suitable for product forms to leave on the hair, or rinse off from the

hair.


PRIMARY OIL

The hair conditioning composition of the present invention comprises a primary oil selected from the group consisting of pentaerythritol ester oils, trimethylol ester oils, and mixtures thereof. The primary oils useful herein are those which are water-insoluble, have a molecular weight of at least about 800, and are in liquid form at 25°C. As used herein, the term "water-insoluble" means the compound is substantially not soluble in water at 25°C; when the compound is mixed with water at a concentration by weight of above 1.0%, preferably at above 0.5%, the compound is temporarily dispersed to form an unstable colloid in water, then is quickly separated from water into two phases.

The primary oil herein provides conditioning benefits such as moisturized feel, smooth feel, and manageability control to the hair when the hair is dried, yet not leave the hair feeling greasy. It is believed that water-insoluble oily material in general are capable of being deposited on the hair. Without being bound by theory, it is believed that, because of its bulkiness, the primary oil covers the surface of the hair and, as a result, the primary oil reduces hair friction to deliver smoothness and manageability control to the hair. It is also believed that, because it has some hydrophilic groups, the primary oil provides moisturized feel, yet, because it is liquid, does not leave the hair feeling greasy. The primary oil is chemically stable under normal use and storage conditions.

The primary oil is preferably included in the composition at a level by weight of from about 0.1% to about 20%, preferably from about 0.2% to about 10%, more preferably from about 0.5% to about 5%.


Pentaerythritol ester oils useful herein are those having the following formula:



wherein R¹, R², R³, and R⁴, independently, are branched, straight, saturated, or unsaturated alkyl, aryl, and alkylaryl groups having from 1 to about 30 carbons. Preferably, R¹, R², R³, and R⁴, independently, are branched, straight, saturated, or unsaturated alkyl groups having from about 8 to about 22 carbons. More

preferably, R^1 , R^2 , R^3 and R^4 are defined so that the molecular weight of the compound is from about 800 to about 1200.

Trimethylol ester oils useful herein are those having the following formula:



5 wherein R^{11} is an alkyl group having from 1 to about 30 carbons, and R^{12} , R^{13} , and R^{14} , independently, are branched, straight, saturated, or unsaturated alkyl, aryl, and alkylaryl groups having from 1 to about 30 carbons. Preferably, R^{11} is ethyl and R^{12} , R^{13} , and R^{14} , independently, are branched, straight, saturated, or unsaturated alkyl groups having from 8 to about 22 carbons. More preferably,
 10 R^{11} , R^{12} , R^{13} and R^{14} are defined so that the molecular weight of the compound is from about 800 to about 1200.

Particularly useful pentaerythritol ester oils and trimethylol ester oils herein include pentaerythritol tetraisostearate, pentaerythritol tetraoleate, trimethylolpropane triisostearate, trimethylolpropane trioleate, and mixtures
 15 thereof. Such compounds are available from Kokyo Alcohol with tradenames KAKPTI, KAKTTI, and Shin-nihon Rika with tradenames PTO, ENUJERUBU TP3SO.

SECONDARY OIL

20 The hair conditioning composition of the present invention comprises a secondary oil selected from the group consisting of poly α -olefin oils, citrate ester oils, glyceryl ester oils, and mixtures thereof. The secondary oils useful herein are those which are water-insoluble, and are in liquid form at 25°C. The term "water-insoluble" is defined in the section above.

The secondary oil enhances the conditioning benefits of the primary oil.
 25 Particularly, it is believed that the secondary oil enhances the smooth feel to the hair when the hair is dried.


The secondary oil is preferably included in the composition at a level by weight of from about 0.1% to about 20%, preferably from about 0.2% to about 10%, more preferably from about 0.5% to about 5%.

30 Poly α -olefin oils useful herein are those derived from 1-alkene monomers having from about 6 to about 16 carbons, preferably from about 6 to about 12

carbons atoms. Nonlimiting examples of 1-alkene monomers useful for preparing the poly α -olefin oils include 1-hexene, 1-octene, 1-decene, 1-dodecene, 1-tetradecene, 1-hexadecene, branched isomers such as 4-methyl-1-pentene, and mixtures thereof. Preferred 1-alkene monomers useful for preparing the poly α -olefin oils are 1-octene, 1-decene, 1-dodecene, 1-tetradecene, 1-hexadecene, and mixtures thereof. Poly α -olefin oils useful herein further have a viscosity of from about 1 to about 35,000 cst, a molecular weight of from about 200 to about 60,000, and a polydispersity of no more than about 3.


Poly α -olefin oils having a molecular weight of at least about 800 are useful herein. Such high molecular weight poly α -olefin oils are believed to provide long lasting moisturized feel to the hair. Poly α -olefin oils having a molecular weight of less than about 800 are useful herein. Such low molecular weight poly α -olefin oils are believed to provide a smooth, light, clean feel to the hair.

Citrate ester oils useful herein are those having a molecular weight of at least about 500 having the following formula:



wherein R^{21} is OH or CH_3COO , and R^{22} , R^{23} , and R^{24} , independently, are branched, straight, saturated, or unsaturated alkyl, aryl, and alkylaryl groups having from 1 to about 30 carbons. Preferably, R^{21} is OH, and R^{22} , R^{23} , and R^{24} , independently, are branched, straight, saturated, or unsaturated alkyl, aryl, and alkylaryl groups having from 8 to about 22 carbons. More preferably, R^{21} , R^{22} , R^{23} and R^{24} are defined so that the molecular weight of the compound is at least about 800.

Glyceryl ester oils useful herein are those having a molecular weight of at least about 500 and having the following formula:



wherein R^{41} , R^{42} , and R^{43} , independently, are branched, straight, saturated, or unsaturated alkyl, aryl, and alkylaryl groups having from 1 to about 30 carbons. Preferably, R^{41} , R^{42} , and R^{43} , independently, are branched, straight, saturated, or unsaturated alkyl, aryl, and alkylaryl groups having from 8 to about 22 carbons. More preferably, R^{41} , R^{42} , and R^{43} are defined so that the molecular weight of the compound is at least about 800.

Particularly useful poly α -olefin oils herein include polydecenes with tradenames PURESYN 6 having a number average molecular weight of about 500 and PURESYN 100 having a number average molecular weight of about 3000 and PURESYN 300 having a number average molecular weight of about 6000 available from Mobil Chemical Co.

Particularly useful citrate ester oils herein include triisocetyl citrate with tradename CITMOL 316 available from Bernel, triisostearyl citrate with tradename PELEMOL TISC available from Phoenix, and trioctyldodecyl citrate with tradename CITMOL 320 available from Bernel.

Particularly useful glyceryl ester oils herein include triisostearin with tradename SUN ESPOL G-318 available from Taiyo Kagaku, triolein with tradename CITHROL GTO available from Croda Surfactants Ltd., trilinolein with tradename EFADERMA-F available from Vevy, or tradename EFA-GLYCERIDES from Brooks.

AQUEOUS CARRIER

The compositions of the present invention comprise an aqueous carrier. The level and species of the carrier are selected according to the compatibility with other components, and other desired characteristic of the product.

Carriers useful in the present invention include water and water solutions of lower alkyl alcohols and polyhydric alcohols. Lower alkyl alcohols useful herein are monohydric alcohols having 1 to 6 carbons, more preferably ethanol and isopropanol. The polyhydric alcohols useful herein include propylene glycol, hexylene glycol, glycerin, and propane diol.

Preferably, the aqueous carrier is substantially water. Deionized water is preferably used. Water from natural sources including mineral cations can also be used, depending on the desired characteristic of the product. Generally, the compositions of the present invention comprise from about 20% to about 95%,
5 preferably from about 30% to about 92%, and more preferably from about 50% to about 90% water..

ADDITIONAL CONDITIONING AGENT

The compositions of the present invention may further comprise an additional conditioning agent. The additional conditioning agents herein are
10 selected from the group consisting of high melting point compounds, cationic surfactants, silicone compounds, and mixtures thereof. The additional conditioning agents herein are used at levels by weight of the composition of from about 0.01% to about 20%, preferably from about 0.1% to about 15%, more preferably from about 1% to about 10%.

High Melting Point Compound

The compositions of the present invention may further comprise a high melting point compound. The high melting point compound useful herein have a melting point of at least about 25°C selected from the group consisting of fatty alcohols, fatty acids, fatty alcohol derivatives, fatty acid derivatives,
20 hydrocarbons, steroids, and mixtures thereof. It is understood by the artisan that the compounds disclosed in this section of the specification can in some instances fall into more than one classification, e.g., some fatty alcohol derivatives can also be classified as fatty acid derivatives. However, a given classification is not intended to be a limitation on that particular compound, but is
25 done so for convenience of classification and nomenclature. Further, it is understood by the artisan that, depending on the number and position of double bonds, and length and position of the branches, certain compounds having certain required carbon atoms may have a melting point of less than about 25°C. Such compounds of low melting point are not intended to be included in this
30 section. Nonlimiting examples of the high melting point compounds are found in International Cosmetic Ingredient Dictionary, Fifth Edition, 1993, and CTFA Cosmetic Ingredient Handbook, Second Edition, 1992.

It is believed that these high melting point compounds cover the hair surface and reduce friction, thereby resulting in providing smooth feel on the hair
35 and ease of combing.

The high melting point compound is preferably included in the composition at a level by weight of from about 1% to about 14%, more preferably from about 3% to about 10%, still preferably from about 4% to about 8%.

The fatty alcohols useful herein are those having from about 14 to about 30 carbon atoms, preferably from about 16 to about 22 carbon atoms. These fatty alcohols can be straight or branched chain alcohols and can be saturated or unsaturated. Nonlimiting examples of fatty alcohols include, cetyl alcohol, stearyl alcohol, behenyl alcohol, and mixtures thereof.

The fatty acids useful herein are those having from about 10 to about 30 carbon atoms, preferably from about 12 to about 22 carbon atoms, and more preferably from about 16 to about 22 carbon atoms. These fatty acids can be straight or branched chain acids and can be saturated or unsaturated. Also included are diacids, triacids, and other multiple acids which meet the requirements herein. Also included herein are salts of these fatty acids. Nonlimiting examples of fatty acids include lauric acid, palmitic acid, stearic acid, behenic acid, sebacic acid, and mixtures thereof.

The fatty alcohol derivatives and fatty acid derivatives useful herein include alkyl ethers of fatty alcohols, alkoxyated fatty alcohols, alkyl ethers of alkoxyated fatty alcohols, esters of fatty alcohols, fatty acid esters of compounds having esterifiable hydroxy groups, hydroxy-substituted fatty acids, and mixtures thereof. Nonlimiting examples of fatty alcohol derivatives and fatty acid derivatives include materials such as methyl stearyl ether; the ceteth series of compounds such as ceteth-1 through ceteth-45, which are ethylene glycol ethers of cetyl alcohol, wherein the numeric designation indicates the number of ethylene glycol moieties present; the steareth series of compounds such as steareth-1 through 10, which are ethylene glycol ethers of steareth alcohol, wherein the numeric designation indicates the number of ethylene glycol moieties present; cetareth 1 through cetareth-10, which are the ethylene glycol ethers of cetareth alcohol, *i.e.* a mixture of fatty alcohols containing predominantly cetyl and stearyl alcohol, wherein the numeric designation indicates the number of ethylene glycol moieties present; C₁-C₃₀ alkyl ethers of the ceteth, steareth, and cetareth compounds just described; polyoxyethylene ethers of behenyl alcohol; ethyl stearate, cetyl stearate, cetyl palmitate, stearyl stearate, myristyl myristate, polyoxyethylene cetyl ether stearate, polyoxyethylene stearyl ether stearate, polyoxyethylene lauryl ether stearate,

ethyleneglycol monostearate, polyoxyethylene monostearate, polyoxyethylene distearate, propyleneglycol monostearate, propyleneglycol distearate, trimethylolpropane distearate, sorbitan stearate, polyglyceryl stearate, glyceryl monostearate, glyceryl distearate, glyceryl tristearate, and mixtures thereof.

5 Hydrocarbons useful herein include compounds having at least about 20 carbons.

Steroids useful herein include compounds such as cholesterol.


High melting point compounds of a single compound of high purity are preferred. Single compounds of pure fatty alcohols selected from the group of
10 pure cetyl alcohol, stearyl alcohol, and behenyl alcohol are highly preferred. By "pure" herein, what is meant is that the compound has a purity of at least about 90%, preferably at least about 95%. These single compounds of high purity provide good rinsability from the hair when the consumer rinses off the composition.

15 Commercially available high melting point compounds useful herein include: cetyl alcohol, stearyl alcohol, and behenyl alcohol having tradenames KONOL series available from Shin Nihon Rika (Osaka, Japan), and NAA series available from NOF (Tokyo, Japan); pure behenyl alcohol having tradename 1-DOCOSANOL available from WAKO (Osaka, Japan), various fatty acids having
20 tradenames NEO-FAT available from Akzo (Chicago Illinois, USA), HYSTRENE available from Witco Corp. (Dublin Ohio, USA), and DERMA available from Vevy (Genova, Italy); and cholesterol having tradename NIKKOL AGUASOME LA available from Nikko.

Cationic Surfactant

25 The compositions of the present invention may further comprise a cationic surfactant. The cationic surfactants useful herein are any known to the artisan, and is preferably included in the composition at a level by weight from about 0.01% to about 20%, more preferably from about 0.05% to about 10%.

Among the cationic surfactants useful herein are those corresponding to
30 the general formula (I):




wherein at least one of R^{101} , R^{102} , R^{103} and R^{104} is selected from an aliphatic group of from 8 to 30 carbon atoms or an aromatic, alkoxy, polyoxyalkylene,

alkylamido, hydroxyalkyl, aryl or alkylaryl group having up to about 22 carbon atoms, the remainder of R^{101} , R^{102} , R^{103} and R^{104} are independently selected from an aliphatic group of from 1 to about 22 carbon atoms or an aromatic, alkoxy, polyoxyalkylene, alkylamido, hydroxyalkyl, aryl or alkylaryl group having up to about 22 carbon atoms; and X is a salt-forming anion such as those selected from halogen, (e.g. chloride, bromide), acetate, citrate, lactate, glycolate, phosphate, nitrate, sulfonate, sulfate, alkylsulfate, and alkyl sulfonate radicals. The aliphatic groups can contain, in addition to carbon and hydrogen atoms, ether linkages, and other groups such as amino groups. The longer chain aliphatic groups, e.g., those of about 12 carbons, or higher, can be saturated or unsaturated. Preferred is when R^{101} , R^{102} , R^{103} and R^{104} are independently selected from C_1 to about C_{22} alkyl. Nonlimiting examples of cationic surfactants useful in the present invention include the materials having the following CTFA designations: quaternium-8, quaternium-14, quaternium-18, quaternium-18 methosulfate, quaternium-24, and mixtures thereof.


Among the cationic surfactants of general formula (I), preferred are those containing in the molecule at least one alkyl chain having at least 16 carbons. Nonlimiting examples of such preferred cationic surfactants include: behenyl trimethyl ammonium chloride available, for example, with tradename INCROQUAT TMC-80 from Croda and ECONOL TM22 from Sanyo Kasei; cetyl trimethyl ammonium chloride available, for example, with tradename CA-2350 from Nikko Chemicals, hydrogenated tallow alkyl trimethyl ammonium chloride, dialkyl (14-18) dimethyl ammonium chloride, ditallow alkyl dimethyl ammonium chloride, dihydrogenated tallow alkyl dimethyl ammonium chloride, distearyl dimethyl ammonium chloride, dicetyl dimethyl ammonium chloride, di(behenyl/arachidyl) dimethyl ammonium chloride, dibehenyl dimethyl ammonium chloride, stearyl dimethyl benzyl ammonium chloride, stearyl propyleneglycol phosphate dimethyl ammonium chloride, stearyl amidopropyl dimethyl benzyl ammonium chloride, stearyl amidopropyl dimethyl (myristylacetate) ammonium chloride, and N-(stearyl colamino formyl methy) pyridinium chloride.

Also preferred are hydrophilically substituted cationic surfactants in which at least one of the substituents contain one or more aromatic, ether, ester, amido, or amino moieties present as substituents or as linkages in the radical chain, wherein at least one of the R^{101} - R^{104} radicals contain one or more



hydrophilic moieties selected from alkoxy (preferably C₁-C₃ alkoxy), polyoxyalkylene (preferably C₁-C₃ polyoxyalkylene), alkylamido, hydroxyalkyl, alkylester, and combinations thereof. Preferably, the hydrophilically substituted cationic conditioning surfactant contains from 2 to about 10 nonionic hydrophile moieties located within the above stated ranges. Preferred hydrophilically substituted cationic surfactants include those of the formula (II) through (VIII) below:




wherein n¹ is from 8 to about 28, m¹+m² is from 2 to about 40, Z¹ is a short chain alkyl, preferably a C₁-C₃ alkyl, more preferably methyl, or (CH₂CH₂O)_{m³}H wherein m¹+m²+m³ is up to 60, and X is a salt forming anion as defined above;




wherein n² is 1 to 5, one or more of R¹⁰⁵, R¹⁰⁶, and R¹⁰⁷ are independently an C₁-C₃₀ alkyl, the remainder are CH₂CH₂OH, one or two of R¹⁰⁸, R¹⁰⁹, and R¹¹⁰ are independently an C₁-C₃₀ alkyl, and remainder are CH₂CH₂OH, and X is a salt forming anion as mentioned above;




wherein, independently for formulae (IV) and (V), Z² is an alkyl, preferably C₁-C₃ alkyl, more preferably methyl, and Z³ is a short chain hydroxyalkyl, preferably hydroxymethyl or hydroxyethyl, n³ and n⁴ independently are integers from 2 to 4, inclusive, preferably from 2 to 3, inclusive, more preferably 2, R¹¹¹ and R¹¹², independently, are substituted or unsubstituted hydrocarbyls, C₁₂-C₂₀ alkyl or alkenyl, and X is a salt forming anion as defined above;



wherein R¹¹³ is a hydrocarbyl, preferably a C₁-C₃ alkyl, more preferably methyl, Z⁴ and Z⁵ are, independently, short chain hydrocarbyls, preferably C₂-C₄ alkyl or alkenyl, more preferably ethyl, m⁴ is from 2 to about 40, preferably from about 7 to about 30, and X is a salt forming anion as defined above;



wherein R¹¹⁴ and R¹¹⁵, independently, are C₁-C₃ alkyl, preferably methyl, Z⁶ is a C₁₂-C₂₂ hydrocarbyl, alkyl carboxy or alkylamido, and A is a protein, preferably a collagen, keratin, milk protein, silk, soy protein, wheat protein, or hydrolyzed forms thereof; and X is a salt forming anion as defined above;



wherein n⁵ is 2 or 3, R¹¹⁶ and R¹¹⁷, independently are C₁-C₃ hydrocarbyls preferably methyl, and X is a salt forming anion as defined above. Nonlimiting examples of hydrophilically substituted cationic surfactants useful in the present invention include the materials having the following CTFA designations: quaternium-16, quaternium-26, quaternium-27, quaternium-30, quaternium-33, quaternium-43, quaternium-52, quaternium-53, quaternium-56, quaternium-60, quaternium-61, quaternium-62, quaternium-70, quaternium-71, quaternium-72, quaternium-75, quaternium-76 hydrolyzed collagen, quaternium-77, quaternium-78, quaternium-79 hydrolyzed collagen, quaternium-79 hydrolyzed keratin, quaternium-79 hydrolyzed milk protein, quaternium-79 hydrolyzed silk, quaternium-79 hydrolyzed soy protein, and quaternium-79 hydrolyzed wheat protein, quaternium-80, quaternium-81, quaternium-82, quaternium-83, quaternium-84, and mixtures thereof.

Highly preferred hydrophilically substituted cationic surfactants include dialkylamido ethyl hydroxyethylmonium salt, dialkylamidoethyl dimonium salt, dialkylol ethyl hydroxyethylmonium salt, dialkylol ethyldimonium salt, and

mixtures thereof; for example, commercially available under the following tradenames; VARISOFT 110, VARISOFT 222, VARIQUAT K1215 and VARIQUAT 638 from Witco Chemical, MACKPRO KLP, MACKPRO WLW, MACKPRO MLP, MACKPRO NSP, MACKPRO NLW, MACKPRO WWP, MACKPRO NLP, MACKPRO SLP from McIntyre, ETHOQUAD 18/25, ETHOQUAD O/12PG, ETHOQUAD C/25, ETHOQUAD S/25, and ETHODUOQUAD from Akzo, DEHYQUAT SP from Henkel, and ATLAS G265 from ICI Americas.

Amines are suitable as cationic surfactants. Primary, secondary, and tertiary fatty amines are useful. Particularly useful are tertiary amido amines having an alkyl group of from about 12 to about 22 carbons. Exemplary tertiary amido amines include: stearamidopropyldimethylamine, stearamidopropyldiethylamine, stearamidoethyldimethylamine, palmitamidopropyldimethylamine, palmitamidopropyldiethylamine, palmitamidoethyldimethylamine, behenamidopropyldimethylamine, behenamidopropyldiethylamine, behenamidoethyldimethylamine, arachidamidopropyldimethylamine, arachidamidopropyldiethylamine, arachidamidoethyldimethylamine, diethylaminoethylstearamide. Also useful are dimethylstearamine, dimethylsoyamine, soyamine, myristylamine, tridecylamine, ethylstearylamine, N-tallowpropane diamine, ethoxylated (with 5 moles of ethylene oxide) stearylamine, dihydroxyethylstearylamine, and arachidylbehenylamine. Useful amines in the present invention are disclosed in U.S. Patent 4,275,055, Nachtigal, et al.

These amines can also be used in combination with acids such as *l*-glutamic acid, lactic acid, hydrochloric acid, malic acid, succinic acid, acetic acid, fumaric acid, tartaric acid, citric acid, *l*-glutamic hydrochloride, maleic acid, and mixtures thereof; more preferably *l*-glutamic acid, lactic acid, citric acid. The amines herein are preferably partially neutralized with any of the acids at a molar ratio of the amine to the acid of from about 1 : 0.3 to about 1 : 2, more preferably from about 1 : 0.4 to about 1 : 1.

Silicone Compound


The compositions of the present invention may further comprise a silicone compound. The silicone compounds useful herein include volatile soluble or

insoluble, or nonvolatile soluble or insoluble silicone conditioning agents. By soluble what is meant is that the silicone compound is miscible with the carrier of the composition so as to form part of the same phase. By insoluble what is meant is that the silicone forms a separate, discontinuous phase from the carrier, such as in the form of an emulsion or a suspension of droplets of the silicone. The silicone compounds herein may be made by any suitable method known in the art, including emulsion polymerization. The silicone compounds may further be incorporated in the present composition in the form of an emulsion, wherein the emulsion is made by mechanical mixing, or in the stage of synthesis through emulsion polymerization, with or without the aid of a surfactant selected from anionic surfactants, nonionic surfactants, cationic surfactants, and mixtures thereof.

The silicone compounds for use herein will preferably have a viscosity of from about 1,000 to about 2,000,000 centistokes at 25°C, more preferably from about 10,000 to about 1,800,000, and even more preferably from about 100,000 to about 1,500,000. The viscosity can be measured by means of a glass capillary viscometer as set forth in Dow Corning Corporate Test Method CTM0004, July 20, 1970. Silicone compound of high molecular weight may be made by emulsion polymerization. Suitable silicone fluids include polyalkyl siloxanes, polyaryl siloxanes, polyalkylaryl siloxanes, polyether siloxane copolymers, and mixtures thereof. Other nonvolatile silicone compounds having hair conditioning properties can also be used.

The silicone compound is preferably included in the composition at a level by weight from about 0.01% to about 20%, more preferably from about 0.05% to about 10%.

The silicone compounds herein also include polyalkyl or polyaryl siloxanes with the following structure (I)



wherein R^{123} is alkyl or aryl, and x is an integer from about 7 to about 8,000. Z^8 represents groups which block the ends of the silicone chains. The alkyl or aryl groups substituted on the siloxane chain (R^{123}) or at the ends of the siloxane chains Z^8 can have any structure as long as the resulting silicone remains fluid at


room temperature, is dispersible, is neither irritating, toxic nor otherwise harmful when applied to the hair, is compatible with the other components of the composition, is chemically stable under normal use and storage conditions, and is capable of being deposited on and conditions the hair. Suitable Z^8 groups include hydroxy, methyl, methoxy, ethoxy, propoxy, and aryloxy. The two R^{123} groups on the silicon atom may represent the same group or different groups. Preferably, the two R^{123} groups represent the same group. Suitable R^{123} groups include methyl, ethyl, propyl, phenyl, methylphenyl and phenylmethyl. The preferred silicone compounds are polydimethylsiloxane, polydiethylsiloxane, and polymethylphenylsiloxane. Polydimethylsiloxane, which is also known as dimethicone, is especially preferred. The polyalkylsiloxanes that can be used include, for example, polydimethylsiloxanes. These silicone compounds are available, for example, from the General Electric Company in their Viscasil® and SF 96 series, and from Dow Corning in their Dow Corning 200 series.

Polyalkylaryl siloxane fluids can also be used and include, for example, polymethylphenylsiloxanes. These siloxanes are available, for example, from the General Electric Company as SF 1075 methyl phenyl fluid or from Dow Corning as 556 Cosmetic Grade Fluid.

Especially preferred, for enhancing the shine characteristics of hair, are highly arylated silicone compounds, such as highly phenylated polyethyl silicone having refractive index of about 1.46 or higher, especially about 1.52 or higher. When these high refractive index silicone compounds are used, they should be mixed with a spreading agent, such as a surfactant or a silicone resin, as described below to decrease the surface tension and enhance the film forming ability of the material.


The silicone compounds that can be used include, for example, a polypropylene oxide modified polydimethylsiloxane although ethylene oxide or mixtures of ethylene oxide and propylene oxide can also be used. The ethylene oxide and polypropylene oxide level should be sufficiently low so as not to interfere with the dispersibility characteristics of the silicone. These material are also known as dimethicone copolyols.

Other silicone compounds include amino substituted materials. Suitable alkylamino substituted silicone compounds include those represented by the following structure (II)




wherein R^{124} is H, CH_3 or OH, p^1 , p^2 , q^1 and q^2 are integers which depend on the molecular weight, the average molecular weight being approximately between 5,000 and 10,000. This polymer is also known as "amodimethicone".

5 Suitable amino substituted silicone fluids include those represented by the formula (III)



10 in which G is chosen from the group consisting of hydrogen, phenyl, OH, C_1 - C_8 alkyl and preferably methyl; a denotes 0 or an integer from 1 to 3, and preferably equals 0; b denotes 0 or 1 and preferably equals 1; the sum $p^3 + p^4$ is a number from 1 to 2,000 and preferably from 50 to 150, p^3 being able to denote a number from 0 to 1,999 and preferably from 49 to 149 and p^4 being able to denote an integer from 1 to 2,000 and preferably from 1 to 10; R^{125} is a monovalent radical of formula $\text{C}_{q^3}\text{H}_{2q^3}\text{L}$ in which q^3 is an integer from 2 to 8 and L is chosen from the

15 groups




20 in which R^{126} is chosen from the group consisting of hydrogen, phenyl, benzyl, a saturated hydrocarbon radical, preferably an alkyl radical containing from 1 to 20 carbon atoms, and X' denotes a halide ion.

An especially preferred amino substituted silicone corresponding to formula (III) is the polymer known as "trimethylsilylamodimethicone wherein R^{124} is CH_3 ."

25

Other amino substituted silicone polymers which can be used are represented by the formula (V):



where R^{128} denotes a monovalent hydrocarbon radical having from 1 to 18 carbon atoms, preferably an alkyl or alkenyl radical such as methyl; R^{129} denotes a hydrocarbon radical, preferably a C_1 - C_{18} alkylene radical or a C_1 - C_{18} , and more preferably C_1 - C_8 , alkyleneoxy radical; Q^- is a halide ion, preferably chloride; p^5 denotes an average statistical value from 2 to 20, preferably from 2 to 8; p^6 denotes an average statistical value from 20 to 200, and preferably from 20 to 50. A preferred polymer of this class is available from Union Carbide under the name "UCAR SILICONE ALE 56."

References disclosing suitable nonvolatile dispersed silicone compounds include U.S. Patent No. 2,826,551, to Geen; U.S. Patent No. 3,964,500, to Drakoff, issued June 22, 1976; U.S. Patent No. 4,364,837, to Pader; and British Patent No. 849,433, to Woolston. "Silicon Compounds" distributed by Petrarch Systems, Inc., 1984, provides an extensive, though not exclusive, listing of suitable silicone compounds.

Another nonvolatile dispersed silicone that can be especially useful is a silicone gum. The term "silicone gum", as used herein, means a polyorganosiloxane material having a viscosity at 25°C of greater than or equal to 1,000,000 centistokes. It is recognized that the silicone gums described herein can also have some overlap with the above-disclosed silicone compounds. This overlap is not intended as a limitation on any of these materials. Silicone gums are described by Petrarch, and others including U.S. Patent No. 4,152,416, to Spitzer *et al.*, issued May 1, 1979 and Noll, Walter, Chemistry and Technology of Silicones, New York: Academic Press 1968. Also describing silicone gums are General Electric Silicone Rubber Product Data Sheets SE 30, SE 33, SE 54 and SE 76. The "silicone gums" will typically have a mass molecular weight in excess of about 200,000, generally between about 200,000 and about 1,000,000. Specific examples include polydimethylsiloxane,

poly(dimethylsiloxane methylvinylsiloxane) copolymer, poly(dimethylsiloxane diphenylsiloxane methylvinylsiloxane) copolymer and mixtures thereof.

Also useful are silicone resins, which are highly crosslinked polymeric siloxane systems. The crosslinking is introduced through the incorporation of tri-
5 functional and tetra-functional silanes with mono-functional or di-functional, or both, silanes during manufacture of the silicone resin. As is well understood in the art, the degree of crosslinking that is required in order to result in a silicone resin will vary according to the specific silane units incorporated into the silicone resin. In general, silicone materials which have a sufficient level of trifunctional
10 and tetrafunctional siloxane monomer units, and hence, a sufficient level of crosslinking, such that they dry down to a rigid, or hard, film are considered to be silicone resins. The ratio of oxygen atoms to silicon atoms is indicative of the level of crosslinking in a particular silicone material. Silicone materials which have at least about 1.1 oxygen atoms per silicon atom will generally be silicone
15 resins herein. Preferably, the ratio of oxygen:silicon atoms is at least about 1.2:1.0. Silanes used in the manufacture of silicone resins include monomethyl-, dimethyl-, trimethyl-, monophenyl-, diphenyl-, methylphenyl-, monovinyl-, and methylvinylchlorosilanes, and tetrachlorosilane, with the methyl substituted silanes being most commonly utilized. Preferred resins are offered by General
20 Electric as GE SS4230 and SS4267. Commercially available silicone resins will generally be supplied in a dissolved form in a low viscosity volatile or nonvolatile silicone fluid. The silicone resins for use herein should be supplied and incorporated into the present compositions in such dissolved form, as will be readily apparent to those skilled in the art. Without being bound by theory, it is
25 believed that the silicone resins can enhance deposition of other silicone compounds on the hair and can enhance the glossiness of hair with high refractive index volumes.

Other useful silicone resins are silicone resin powders such as the material given the CTFA designation polymethylsilsequioxane, which is
30 commercially available as Tospearl™ from Toshiba Silicones.

The method of manufacturing these silicone compounds, can be found in Encyclopedia of Polymer Science and Engineering, Volume 15, Second Edition, pp. 204-308, John Wiley & Sons, Inc., 1989.

Silicone materials and silicone resins in particular, can conveniently be
35 identified according to a shorthand nomenclature system well known to those

skilled in the art as the "MDTQ" nomenclature. Under this system, the silicone is described according to the presence of various siloxane monomer units which make up the silicone. Briefly, the symbol M denotes the mono-functional unit $(\text{CH}_3)_3\text{SiO}_{0.5}$; D denotes the difunctional unit $(\text{CH}_3)_2\text{SiO}$; T denotes the trifunctional unit $(\text{CH}_3)\text{SiO}_{1.5}$; and Q denotes the quadri- or tetra-functional unit SiO_2 . Primes of the unit symbols, e.g., M', D', T', and Q' denote substituents other than methyl, and must be specifically defined for each occurrence. Typical alternate substituents include groups such as vinyl, phenyl, amino, hydroxyl, etc. The molar ratios of the various units, either in terms of subscripts to the symbols indicating the total number of each type of unit in the silicone, or an average thereof, or as specifically indicated ratios in combination with molecular weight, complete the description of the silicone material under the MDTQ system. Higher relative molar amounts of T, Q, T' and/or Q' to D, D', M and/or M' in a silicone resin is indicative of higher levels of crosslinking. As discussed before, however, the overall level of crosslinking can also be indicated by the oxygen to silicon ratio.

The silicone resins for use herein which are preferred are MQ, MT, MTQ, MQ and MDTQ resins. Thus, the preferred silicone substituent is methyl. Especially preferred are MQ resins wherein the M:Q ratio is from about 0.5:1.0 to about 1.5:1.0 and the average molecular weight of the resin is from about 1000 to about 10,000.

Commercially available silicone compounds which are useful herein include Dimethicone with tradename D-130, cetyl Dimethicone with tradename DC2502, stearyl Dimethicone with tradename DC2503, emulsified polydimethyl siloxanes with tradenames DC1664 and DC1784, and alkyl grafted copolymer silicone emulsion with tradename DC2-2845; all available from Dow Corning Corporation, and emulsion polymerized Dimethiconol available from Toshiba Silicone as described in GB application 2,303,857.

ADDITIONAL COMPONENTS

The compositions of the present invention may include a variety of additional components, which may be selected by the artisan according to the desired characteristics of the final product. Additional components include, for example, cationic polymers, additional oily compounds, nonionic polymers, and other additional components.

Cationic Polymers

The hair conditioning compositions of the present invention may contain one or more cationic polymers. As used herein, the term "polymer" shall include materials whether made by polymerization of one type of monomer or made by two (*i.e.*, copolymers) or more types of monomers.

Preferably, the cationic polymer is a water-soluble cationic polymer. By "water soluble" cationic polymer, what is meant is a polymer which is sufficiently soluble in water to form a substantially clear solution to the naked eye at a concentration of 0.1% in water (distilled or equivalent) at 25°C. The preferred polymer will be sufficiently soluble to form a substantially clear solution at 0.5% concentration, more preferably at 1.0% concentration.

The cationic polymers hereof will generally have a weight average molecular weight which is at least about 5,000, typically at least about 10,000, and is less than about 10 million. Preferably, the molecular weight is from about 100,000 to about 2 million. The cationic polymers will generally have cationic nitrogen-containing moieties such as quaternary ammonium or cationic amino moieties, and mixtures thereof.

The cationic charge density is preferably at least about 0.1 meq/gram, more preferably at least about 1.5 meq/gram, even more preferably at least about 1.1 meq/gram, still more preferably at least about 1.2 meq/gram. Cationic charge density of the cationic polymer can be determined according to the Kjeldahl Method. Those skilled in the art will recognize that the charge density of amino-containing polymers may vary depending upon pH and the isoelectric point of the amino groups. The charge density should be within the above limits at the pH of intended use.

Any anionic counterions can be utilized for the cationic polymers so long as the water solubility criteria is met. Suitable counterions include halides (*e.g.*, Cl, Br, I, or F, preferably Cl, Br, or I), sulfate, and methylsulfate. Others can also be used, as this list is not exclusive.

The cationic nitrogen-containing moiety will be present generally as a substituent, on a fraction of the total monomer units of the cationic hair conditioning polymers. Thus, the cationic polymer can comprise copolymers, terpolymers, etc. of quaternary ammonium or cationic amine-substituted monomer units and other non-cationic units referred to herein as spacer monomer units. Such polymers are known in the art, and a variety can be found

in the CTFA Cosmetic Ingredient Dictionary, 3rd edition, edited by Estrin, Crosley, and Haynes, (The Cosmetic, Toiletry, and Fragrance Association, Inc., Washington, D.C., 1982).

Suitable cationic polymers include, for example, copolymers of vinyl
5 monomers having cationic amine or quaternary ammonium functionalities with water soluble spacer monomers such as acrylamide, methacrylamide, alkyl and dialkyl acrylamides, alkyl and dialkyl methacrylamides, alkyl acrylate, alkyl methacrylate, vinyl caprolactone, and vinyl pyrrolidone. The alkyl and dialkyl substituted monomers preferably have $C_1 - C_7$ alkyl groups, more preferably $C_1 - C_3$ alkyl groups. Other suitable spacer monomers include vinyl esters, vinyl
10 alcohol (made by hydrolysis of polyvinyl acetate), maleic anhydride, propylene glycol, and ethylene glycol.

The cationic amines can be primary, secondary, or tertiary amines, depending upon the particular species and the pH of the composition. In
15 general, secondary and tertiary amines, especially tertiary amines, are preferred.


Amine-substituted vinyl monomers can be polymerized in the amine form, and then optionally can be converted to ammonium by a quaternization reaction. Amines can also be similarly quaternized subsequent to formation of the polymer. For example, tertiary amine functionalities can be quaternized by
20 reaction with a salt of the formula $R^{118}X$ wherein R^{118} is a short chain alkyl, preferably a $C_1 - C_7$ alkyl, more preferably a $C_1 - C_3$ alkyl, and X is a salt forming anion as defined above.

Suitable cationic amino and quaternary ammonium monomers include, for example, vinyl compounds substituted with dialkylaminoalkyl acrylate,
25 dialkylaminoalkyl methacrylate, monoalkylaminoalkyl acrylate, monoalkylaminoalkyl methacrylate, trialkyl methacryloxyalkyl ammonium salt, trialkyl acryloxyalkyl ammonium salt, diallyl quaternary ammonium salts, and vinyl quaternary ammonium monomers having cyclic cationic nitrogen-containing rings such as pyridinium, imidazolium, and quaternized pyrrolidone, e.g., alkyl vinyl
30 imidazolium, alkyl vinyl pyridinium, alkyl vinyl pyrrolidone salts. The alkyl portions of these monomers are preferably lower alkyls such as the $C_1 - C_3$ alkyls, more preferably C_1 and C_2 alkyls. Suitable amine-substituted vinyl monomers for use herein include dialkylaminoalkyl acrylate, dialkylaminoalkyl methacrylate, dialkylaminoalkyl acrylamide, and dialkylaminoalkyl methacrylamide, wherein the
35 alkyl groups are preferably $C_1 - C_7$ hydrocarbyls, more preferably $C_1 - C_3$ alkyls.

The cationic polymers hereof can comprise mixtures of monomer units derived from amine- and/or quaternary ammonium-substituted monomer and/or compatible spacer monomers.

Suitable cationic hair conditioning polymers include, for example: copolymers of 1-vinyl-2-pyrrolidone and 1-vinyl-3-methylimidazolium salt (e.g., chloride salt) (referred to in the industry by the Cosmetic, Toiletry, and Fragrance Association, "CTFA", as Polyquaternium-16), such as those commercially available from BASF Wyandotte Corp. (Parsippany, NJ, USA) under the LUVIQUAT tradename (e.g., LUVIQUAT FC 370); copolymers of 1-vinyl-2-pyrrolidone and dimethylaminoethyl methacrylate (referred to in the industry by CTFA as Polyquaternium-11) such as those commercially available from Gaf Corporation (Wayne, NJ, USA) under the GAFQUAT tradename (e.g., GAFQUAT 755N); cationic diallyl quaternary ammonium-containing polymers, including, for example, dimethyldiallylammonium chloride homopolymer and copolymers of acrylamide and dimethyldiallylammonium chloride, referred to in the industry (CTFA) as Polyquaternium 6 and Polyquaternium 7, respectively; and mineral acid salts of amino-alkyl esters of homo- and co-polymers of unsaturated carboxylic acids having from 3 to 5 carbon atoms, as described in U.S. Patent 4,009,256.


Other suitable cationic polymers are amphoteric terpolymers consisting of acrylic acid methacrylamidopropyl trimethylammonium chloride and methyl acrylate, having a structure as shown below referred to in the industry (CTFA) as Polyquaternium 47. An example of a suitable commercial material is MERQUAT 2001® wherein the ratio of $n^6:n^7:n^8$ is 45:45:10 supplied by Calgon Corp.



Other cationic polymers that can be used include polysaccharide polymers, such as cationic cellulose derivatives and cationic starch derivatives.

Cationic polysaccharide polymer materials suitable for use herein include

those of the formula:



wherein: Z^7 is an anhydroglucose residual group, such as a starch or cellulose
 5 anhydroglucose residual, R^{119} is an alkylene oxyalkylene, polyoxyalkylene, or
 hydroxyalkylene group, or combination thereof, R^{120} , R^{121} , and R^{122} independently
 are alkyl, aryl, alkylaryl, arylalkyl, alkoxyalkyl, or alkoxyaryl groups, each group
 containing up to about 18 carbon atoms, and the total number of carbon atoms
 for each cationic moiety (*i.e.*, the sum of carbon atoms in R^{120} , R^{121} and R^{122})
 10 preferably being about 20 or less, and X is as previously described.

Cationic cellulose is available from Amerchol Corp. (Edison, NJ, USA) in
 their Polymer JR® and LR® series of polymers, as salts of hydroxyethyl cellulose
 reacted with trimethyl ammonium substituted epoxide, referred to in the industry
 (CTFA) as Polyquaternium 10. Another type of cationic cellulose includes the
 15 polymeric quaternary ammonium salts of hydroxyethyl cellulose reacted with
 lauryl dimethyl ammonium-substituted epoxide, referred to in the industry (CTFA)
 as Polyquaternium 24. These materials are available from Amerchol Corp.
 (Edison, NJ, USA) under the tradename Polymer LM-200®.

Other cationic polymers that can be used include cationic guar gum
 20 derivatives, such as guar hydroxypropyltrimonium chloride commercially
 available from Celanese Corp. in their Jaguar R series. Other materials include
 quaternary nitrogen-containing cellulose ethers as described in U.S. Patent
 3,962,418, and copolymers of etherified cellulose and starch as described in U.S.
 Patent 3,958,581.

25 Particularly useful cationic polymers herein include Polyquaternium-7,
 Polyquaternium-10, Polyquaternium-24, Polyquaternium-39, Polyquaternium-47,
 and mixtures thereof.

Additional Oily Compounds

30 Additional oily compounds useful herein include fatty alcohols and their
 derivatives, fatty acids and their derivatives, and hydrocarbons. The additional
 oily compounds useful herein may be volatile or nonvolatile, and have a melting
 point of not more than about 25°C. Without being bound by theory, it is believed
 that, the additional oily compounds may penetrate into the hair to modify the

hydroxy bonds of the hair, thereby resulting in providing softness and flexibility to the hair. The additional oily compounds of this section are to be distinguished from the high melting point compounds described above. Nonlimiting examples of the additional oily compounds are found in International Cosmetic Ingredient Dictionary, Fifth Edition, 1993, and CTFA Cosmetic Ingredient Handbook, Second Edition, 1992.

The fatty alcohols useful herein include those having from about 10 to about 30 carbon atoms, preferably from about 12 to about 22 carbon atoms, and more preferably from about 16 to about 22 carbon atoms. These fatty alcohols can be straight or branched chain alcohols and can be saturated or unsaturated alcohols, preferably unsaturated alcohols. Nonlimiting examples of these compounds include oleyl alcohol, palmitoleic alcohol, isostearyl alcohol, isocetyl alcohol, undecanol, octyl dodecanol, octyl decanol, octyl alcohol, caprylic alcohol, decyl alcohol and lauryl alcohol.

The fatty acids useful herein include those having from about 10 to about 30 carbon atoms, preferably from about 12 to about 22 carbon atoms, and more preferably from about 16 to about 22 carbon atoms. These fatty acids can be straight or branched chain acids and can be saturated or unsaturated. Suitable fatty acids include, for example, oleic acid, linoleic acid, isostearic acid, linolenic acid, ethyl linolenic acid, ethyl linolenic acid, arachidonic acid, and ricinolic acid.

The fatty acid derivatives and fatty alcohol derivatives are defined herein to include, for example, esters of fatty alcohols, alkoxylated fatty alcohols, alkyl ethers of fatty alcohols, alkyl ethers of alkoxylated fatty alcohols, and bulky ester oils such as pentaerythritol ester oils, trimethylol ester oils, citrate ester oils, glyceryl ester oils, and mixtures thereof. Nonlimiting examples of fatty acid derivatives and fatty alcohol derivatives, include, for example, methyl linoleate, ethyl linoleate, isopropyl linoleate, isodecyl oleate, isopropyl oleate, ethyl oleate, octyldodecyl oleate, oleyl oleate, decyl oleate, butyl oleate, methyl oleate, octyldodecyl stearate, octyldodecyl isostearate, octyldodecyl isopalmitate, octyl isopelargonate, octyl pelargonate, hexyl isostearate, isopropyl isostearate, isodecyl isononanoate, isopropyl isostearate, ethyl isostearate, methyl isostearate and Oleth-2. Bulky ester oils such as pentaerythritol ester oils, trimethylol ester oils, citrate ester oils and glyceryl ester oils useful herein are those which have a molecular weight of less than about 800, preferably less than about 500.

The hydrocarbons useful herein include straight chain, cyclic, and branched chain hydrocarbons which can be either saturated or unsaturated, so long as they have a melting point of not more than about 25°C. These hydrocarbons have from about 12 to about 40 carbon atoms, preferably from about 12 to about 30 carbon atoms, and preferably from about 12 to about 22 carbon atoms. Also encompassed herein are polymeric hydrocarbons of alkenyl monomers, such as polymers of C₂₋₆ alkenyl monomers. These polymers can be straight or branched chain polymers. The straight chain polymers will typically be relatively short in length, having a total number of carbon atoms as described above. The branched chain polymers can have substantially higher chain lengths. The number average molecular weight of such materials can vary widely, but will typically be up to about 500, preferably from about 200 to about 400, and more preferably from about 300 to about 350. Also useful herein are the various grades of mineral oils. Mineral oils are liquid mixtures of hydrocarbons that are obtained from petroleum. Specific examples of suitable hydrocarbon materials include paraffin oil, mineral oil, dodecane, isododecane, hexadecane, isohexadecane, eicosene, isoeicosene, tridecane, tetradecane, polybutene, polyisobutene, and mixtures thereof. Preferred for use herein are hydrocarbons selected from the group consisting of mineral oil, poly α -olefin oils such as isododecane, isohexadecane, polybutene, polyisobutene, and mixtures thereof.


Commercially available fatty alcohols and their derivatives useful herein include: oleyl alcohol with tradename UNJECOL 90BHR available from Shin Nihon Rika, various liquid esters with tradenames SCHERCEMOL series available from Scher, and hexyl isostearate with a tradename HIS and isopropyl isostearate having a tradename ZPIS available from Kokyu Alcohol. Commercially available bulky ester oils useful herein include: trimethylolpropane tricaprilate/tricaprate with tradename MOBIL ESTER P43 from Mobil Chemical Co. Commercially available hydrocarbons useful herein include isododecane, isohexadecane, and isoeicosene with tradenames PERMETHYL 99A, PERMETHYL 101A, and PERMETHYL 1082, available from Presperse (South Plainfield New Jersey, USA), a copolymer of isobutene and normal butene with tradenames INDOPOL H-100 available from Amoco Chemicals (Chicago Illinois, and USA), mineral oil with tradename BENOL available from Witco, isoparaffin with tradename ISOPAR from Exxon Chemical Co. (Houston Texas, USA).

Nonionic Polymers

Nonionic polymers useful herein include cellulose derivatives, hydrophobically modified cellulose derivatives, ethylene oxide polymers, and ethylene oxide/propylene oxide based polymers. Suitable nonionic polymers are cellulose derivatives including methylcellulose with tradename BENECEL, hydroxyethyl cellulose with tradename NATROSOL, hydroxypropyl cellulose with tradename KLUCEL, cetyl hydroxyethyl cellulose with tradename POLYSURF 67, all supplied by Hercules. Other suitable nonionic polymers are ethylene oxide and/or propylene oxide based polymers with tradenames CARBOWAX PEGs, POLYOX WASRs, and UCON FLUIDS, all supplied by Amerchol.

Polyethylene Glycols

The polyalkylene glycols are characterized by the general formula:



wherein R^{201} is selected from the group consisting of H, methyl, and mixtures thereof. When R^{201} is H, these materials are polymers of ethylene oxide, which are also known as polyethylene oxides, polyoxyethylenes, and polyethylene glycols. When R^{201} is methyl, these materials are polymers of propylene oxide, which are also known as polypropylene oxides, polyoxypropylenes, and polypropylene glycols. When R^{201} is methyl, it is also understood that various positional isomers of the resulting polymers can exist.

In the above structure, $x3$ has an average value of from about 1500 to about 25,000, preferably from about 2500 to about 20,000, and more preferably from about 3500 to about 15,000.

Other useful polymers include the polypropylene glycols and mixed polyethylene/polypropylene glycols.

Polyethylene glycol polymers useful herein are PEG-2M wherein R^{201} equals H and $x3$ has an average value of about 2,000 (PEG-2M is also known as Polyox WSR® N-10, which is available from Union Carbide and as PEG-2,000); PEG-5M wherein R^{201} equals H and $x3$ has an average value of about 5,000 (PEG-5M is also known as Polyox WSR® N-35 and Polyox WSR® N-80, both available from Union Carbide and as PEG-5,000 and Polyethylene Glycol 300,000); PEG-7M wherein R^{201} equals H and $x3$ has an average value of about 7,000 (PEG-7M is also known as Polyox WSR® N-750 available from Union

Carbide); PEG-9M wherein R²⁰¹ equals H and x3 has an average value of about 9,000 (PEG 9-M is also known as Polyox WSR® N-3333 available from Union Carbide); and PEG-14 M wherein R²⁰¹ equals H and x3 has an average value of about 14,000 (PEG-14M is also known as Polyox WSR® N-3000 available from Union Carbide).

Other Additional Components

The compositions of the present invention may include other additional components, which may be selected by the artisan according to the desired characteristics of the final product and which are suitable for rendering the composition more cosmetically or aesthetically acceptable or to provide them with additional usage benefits. Such other additional components generally are used individually at levels of from about 0.001% to about 10%, preferably up to about 5% by weight of the composition.

A wide variety of other additional components can be formulated into the present compositions. These include: other conditioning agents such as hydrolysed collagen with tradename Peptin 2000 available from Hormel, vitamin E with tradename Emix-d available from Eisai, panthenol available from Roche, panthenyl ethyl ether available from Roche, hydrolysed keratin, proteins, plant extracts, and nutrients; hair-fixative polymers such as amphoteric fixative polymers, cationic fixative polymers, anionic fixative polymers, nonionic fixative polymers, and silicone grafted copolymers; preservatives such as benzyl alcohol, methyl paraben, propyl paraben and imidazolidinyl urea; pH adjusting agents, such as citric acid, sodium citrate, succinic acid, phosphoric acid, sodium hydroxide, sodium carbonate; salts, in general, such as potassium acetate and sodium chloride; coloring agents, such as any of the FD&C or D&C dyes; hair oxidizing (bleaching) agents, such as hydrogen peroxide, perborate and persulfate salts; hair reducing agents such as the thioglycolates; perfumes; and sequestering agents, such as disodium ethylenediamine tetra-acetate; ultraviolet and infrared screening and absorbing agents such as octyl salicylate, antidandruff agents such as zinc pyridinethione; and optical brighteners, for example polystyrylstilbenes, triazinstilbenes, hydroxycoumarins, aminocoumarins, triazoles, pyrazolines, oxazoles, pyrenes, porphyrins, imidazoles, and mixtures thereof.

EXAMPLES

The following examples further describe and demonstrate embodiments within the scope of the present invention. The examples are given solely for the purpose of illustration and are not to be construed as limitations of the present invention, as many variations thereof are possible without departing from the spirit and scope of the invention. Ingredients are identified by chemical or CTFA name, or otherwise defined below.

The compositions of the present invention are suitable for rinse-off products and leave-on products, and are particularly useful for making products in the form of emulsion, cream, gel, spray or, mousse.

Examples 1 through 6 are hair conditioning compositions of the present invention which are particularly useful for rinse-off use.

Compositions

Components	Ex. 1	Ex. 2	Ex. 3	Ex. 4	Ex. 5	Ex. 6
Pentaerythritol Tetraisostearate *1	1.0	1.0	1.0	-	-	-
Pentaerythritol Tetraoleate *2	-	-	0.5	-	-	-
Trimethylolpropane Trioleate *3	-	-	-	1.0	1.0	1.0
Trimethylolpropane Triisostearate *4	-	-	-	-	-	0.5
Poly α -olefin oil-1 *5	1.0	-	-	-	-	-
Poly α -olefin oil-2 *6	-	1.0	-	-	-	-
Triisostearyl Citrate	-	-	1.0	-	-	-
Triisocetyl Citrate *7	-	-	-	1.0	-	-
Glyceryl trioleate *8	-	-	-	-	1.0	-
Glyceryl triisostearate *9	-	-	-	-	-	1.0
Cetyl Alcohol *10	4.5	6.0	4.0	4.0	4.5	1.0
Stearyl Alcohol *11	2.5	1.0	2.0	2.5	2.5	6.0
Behenyl Alcohol *12	-	1.0	-	1.0	0.5	-
Dihydrogenated Tallowamidoethyl Hydroxyethylmonium Methosulfate *13	1.0	1.0	-	-	-	1.0
Distearamidoethyl hydroxyethylmonium methosulfate	-	-	1.0	1.0	1.0	-
Stearamidopropyl Dimethylamine *14	2.0	2.0	2.0	2.0	2.0	2.0
<i>l</i> -Glutamic Acid *15	0.64	0.64	0.8	0.6	0.64	0.64
Hydroxyethyl Cellulose *16	-	-	-	-	0.5	0.1
Polyoxyethylene (2000) *17	0.1	-	0.1	-	-	-
Polyquaternium-10 *18	-	-	-	-	0.05	0.05
Polyquaternium-7 *19	-	-	-	0.05	-	-
Preservatives	0.04	0.04	0.04	0.04	0.04	0.04

Benzyl alcohol	0.4	0.4	0.4	0.4	0.4	0.4
Perfume	0.25	0.25	0.25	0.25	0.25	0.25
Silicone Blend *20	2.0	2.5	4.2	2.5	2.5	2.5
Silicone Emulsion *21	-	-	-	0.5	0.5	0.5
Hydrolyzed collagen *22	0.01	0.01	0.01	0.01	0.01	0.01
Vitamin E *23	0.01	0.01	0.01	0.01	0.01	0.01
Panthenol *24	0.03	0.03	0.03	0.03	0.03	0.03
Panthenyl Ethyl Ether *25	0.25	0.25	0.25	0.25	0.25	0.25
Citric Acid *26	amount necessary to adjust pH 3-7					
Deionized Water	-----q.s. to 100%-----					

Definitions of Components

- *1 Pentaerythritol Tetraisostearate: KAK PTI obtained by Kokyu alcohol.
- *2 Pentaerythritol Tetraoleate: Available from Shin NihonRika.
- *3 Trimethylolpropane Trioleate: Enujerubu TP3SO obtained by Shin NihonRika.
- *4 Trimethylolpropane Triisostearate: KAK TTI obtained by Kokyu alcohol.
- *5 Poly α -olefin oil-1: Puresyn 6 obtained by Mobil.
- *6 Poly α -olefin oil-2: Puresyn 300 obtained by Mobil.
- *7 Triisocetyl Citrate: Available from Bernel.
- *8 Glyceryl trioleate: Available from Witco
- *9 Glyceryl triisostearate: Available from Taiyo Kagaku.
- *10 Cetyl Alcohol: Konol series obtained by Shin Nihon Rika.
- *11 Stearyl Alcohol: Konol series obtained by Shin NihonRika.
- *12 Behenyl Alcohol: 1-Docosanol (97%) obtained by Wako.
- *13 Dihydrogenated Tallowamidoethyl Hydroxyethylmonium Methosulfate: Varisoft 110 obtained by Witco.
- *14 Stearamidopropyl Dimethylamine: Amidoamine MPS obtained by Nikko.
- *15 *l*-Glutamic Acid: *l*-Glutamic acid (cosmetic grade) obtained by Ajinomoto.
- *16 Hydroxyethyl Cellulose: Available from Aqualon.
- *17 Polyoxyethylene (2000): WSR N-10 obtained Amerchol.
- *18 Polyquaternium-10: UCARE Polymer LR 400 obtained by Amerchol.
- *19 Polyquaternium-7: MerquatS obtained by Calgon.
- *20 Silicone Blend: SE76 obtained by G.E.
- *21 Silicone Emulsion: X65-4829 obtained by Tosil/GE.
- *22 Hydrolyzed collagen: Peptin 2000 obtained by Hormel.
- *23 Vitamin E: Emix-d obtained by Eisai.

*24 Panthenol: Available from Roche.

*25 Panthenyl Ethyl Ether: Available from Roche.

*26 Citric Acid: Anhydrous Citric acid obtained by Haarman & Reimer.

Method of Preparation

5 The compositions of Examples 1 through 6 as shown above can be prepared by any conventional method well known in the art. They are suitably made as follows: If included in the composition, polymeric materials such as hydroxyethyl cellulose, polyoxyethylene, Polyquaternium-10, and Polyquaternium-7 are dispersed in water at room temperature to make a polymer
10 solution. High melting point compounds, hydrophilically substituted cationic surfactant, tertiary amido amines, and the polymer solution, if present, are mixed and heated up to above 70°C. The mixture thus obtained is cooled down to below 50°C, and the remaining components are added with agitation, and further cooled down to about 30°C.

15 Alternatively, high melting point compounds, tertiary amido amines, and the polymer solution, if present, are mixed and heated up to above 70°C. The mixture thus obtained is cooled down to about 60°C where the hydrophilically substituted cationic surfactant is added. The final mixtures thus obtained is cooled below 50°C, and the remaining components are added with agitation, and
20 further cooled down to about 30°C.

A triblender and/or mill can be used in each step, if necessary to disperse the materials.

25 The embodiments disclosed and represented by the previous examples have many advantages. For example, they can provide long lasting moisturized feel, smooth feel, and manageability control to the hair when the hair is dried, yet not leave the hair feeling greasy.


It is understood that the examples and embodiments described herein are for illustrative purposes only and that various modifications or changes in light
30 thereof will be suggested to one skilled in the art without departing from its spirit and scope.

WHAT IS CLAIMED IS:

1. A hair conditioning composition comprising:


(1) a primary oil being water-insoluble, having a molecular weight of at least about 800, and in liquid form at 25°C, the primary oil selected from the group consisting of:

5 a) pentaerythritol ester oils of the following formula:



wherein R¹, R², R³, and R⁴, independently, are branched, straight, saturated, or unsaturated alkyl, aryl, and alkylaryl groups having from 1 to about 30 carbons;

10 b) trimethylol ester oils of the following formula:




wherein R¹¹ is an alkyl group having from 1 to about 30 carbons, and R¹², R¹³, and R¹⁴, independently, are branched, straight, saturated, or unsaturated alkyl, aryl, and alkylaryl groups having from 1 to about 30 carbons;

15 and mixtures thereof;

(2) a secondary oil selected from the group consisting of:


20 c) poly α-olefin oils derived from 1-alkene monomers having from about 6 to about 16 carbons, the poly α-olefin oils having a viscosity of from about 1 to about 35,000 cst, a molecular weight of from about 200 to about 60,000, and a polydispersity of no more than about 3;

25 d) citrate ester oils being water-insoluble, having a molecular weight of at least about 500, and in liquid form at 25°C and having the following formula:



wherein R^{21} is OH or CH_3COO , and R^{22} , R^{23} , and R^{24} , independently, are branched, straight, saturated, or unsaturated alkyl, aryl, and alkylaryl groups having from 1 to about 30 carbons;

e) glyceryl ester oils being water-insoluble, having a molecular weight of at least about 500, and in liquid form at 25°C and having the following formula:



wherein R^{41} , R^{42} , and R^{43} , independently, are branched, straight, saturated, or unsaturated alkyl, aryl, and alkylaryl groups having from 1 to about 30 carbons;

and mixtures thereof; and

(3) an aqueous carrier.

2. The hair conditioning composition according to Claim 1 wherein the primary oil is selected from the group consisting of pentaerythritol ester oils wherein R^1 , R^2 , R^3 , and R^4 , independently, are branched, straight, saturated, or unsaturated alkyl groups having from about 8 to about 22 carbons, trimethylol ester oils wherein R^{11} is ethyl and R^{12} , R^{13} , and R^{14} , independently, are branched, straight, saturated, or unsaturated alkyl groups having from 8 to about 22 carbons; and mixtures thereof.

3. The hair conditioning composition according to Claim 1 wherein the secondary oil is selected from poly α -olefin oils having a molecular weight of less than about 800.

4. The hair conditioning composition according to Claim 1 wherein the secondary oil has a molecular weight of at least about 800.
5. The hair conditioning composition according to Claim 1 comprising by weight from about 0.5% to about 5% of the primary oil and from about 0.5% to about 5% of the secondary oil.
6. The hair conditioning composition according to any of the preceding claims further comprising an additional conditioning agent selected from the group consisting of high melting point compounds, cationic surfactants, silicone compounds, and mixtures thereof.

INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 98/11785

A. CLASSIFICATION OF SUBJECT MATTER

IPC 6 A61K7/06

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 A61K

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO 97 35546 A (PROCTER & GAMBLE) 2 October 1997 see claims 1-9; examples 11-15 ---	1-6
A	WO 97 35547 A (PROCTER & GAMBLE) 2 October 1997 see examples 6-10 ---	1-6
A	US 5 578 298 A (BERTHIAUME ET AL.) 26 November 1996 see the whole document ---	1-6
A	WO 95 00107 A (AMINCO INC) 5 January 1995 see the whole document ---	1-6
A	DE 43 37 169 A (HARTMANN-HAARKOSMETIK) 4 May 1995 see the whole document ---	1-6
-/--		

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

22 March 1999

Date of mailing of the international search report

30/03/1999

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Fischer, J.P.

INTERNATIONAL SEARCH REPORT

Int. Application No.

PCT/US 98/11785

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	<p>EP 0 547 897 A (UNILEVER) 23 June 1993 see the whole document -----</p>	1-6

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US 98/11785

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 9735546 A	02-10-1997	AU 2320097 A CA 2250388 A	17-10-1997 02-10-1997
WO 9735547 A	02-10-1997	AU 2320297 A	17-10-1997
US 5578298 A	26-11-1996	US 5683625 A DE 19518449 A FR 2720401 A GB 2289686 A.B JP 8059994 A	04-11-1997 30-11-1995 01-12-1995 29-11-1995 05-03-1996
WO 9500107 A	05-01-1995	US 5437860 A AU 7061394 A BR 9406954 A CA 2165952 A EP 0705094 A ZA 9404471 A	01-08-1995 17-01-1995 20-08-1996 05-01-1995 10-04-1996 14-02-1995
DE 4337169 A	04-05-1995	NONE	
EP 547897 A	23-06-1993	AU 3029992 A BR 9205076 A CA 2085411 A JP 5255039 A ZA 9209774 A	24-06-1993 20-07-1993 20-06-1993 05-10-1993 17-06-1994